



# PILLOW CASE

Standard Pillow Case	
Fabric Requirements	
Main Fabric	¾ Yd.
Cuff	⅓ Yd.
Accent Fabric	⅛ Yd.
Cutting	
Main Fabric	26" x 45" Width of Fabric(WOF)
Cuff	10" x 45" WOF
Accent Fabric	2" x 45" WOF

Travel Pillow Case	
Fabric Requirements	
Main Fabric	5/8 Yd.
Cuff	⅓ Yd.
Accent Fabric	⅛ Yd.
Cutting	
Main Fabric	18" x 30"
Cuff	10" x 30"
Accent Fabric	2" x 30"

## Directions

1. Fold accent fabric in half, lengthwise. Wrong sides together.
2. Machine baste folded accent strip onto the top edge of main fabric. Use ⅛" seam allowance.
3. Sew the cuff onto the top edge of the main fabric. (Using the "Hot Dog" method.)
  - ◆ With right sides together, sew the cuff (lengthwise) onto the top edge of the main fabric. Stitch through cuff, folded accent fabric and main fabric. Use ¼" seam allowance.
  - ◆ Lay pillow case flat with the cuff flipped up. The right sides of cuff and main fabric should be facing up.
  - ◆ Starting at the bottom, roll the main fabric into a long, skinny tube. Roll until it meets the accent fabric strip.
  - ◆ Wrap the cuff around the long skinny tube, creating the "Hot Dog". The right sides of the cuff fabric should be facing one another. The wrong side of the cuff should be facing out.
  - ◆ Using a generous ¼" seam, stitch cuff edges together. Sew through the cuff fabric, the accent strip, and main fabric.
  - ◆ Turn "Hot Dog" inside out. Hooray! The cuff and accent fabric are stitched on with a neatly encased seam.
4. Complete the pillow case (using a French seam).
  - ◆ Fold the pillow case in half, lengthwise, **wrong sides together**. Stitch the side seam with a ¼" seam. Press.
  - ◆ Turn the pillow case so the right sides are together. Again stitch the side seam. This time with a ½" seam allowance.
  - ◆ Stitch across the bottom of the pillow case with a ½" seam allowance.
5. Turn right side out. Press. Pillow case completed.